


VDS[®] by FORSTER[®] LITE DOORS

20, 45, 60, 90 Minute Door Assemblies

CLASSIFICATION

PRODUCT DESCRIPTION



VDS Lite doors keep a narrow profile allowing for maximum vision area. These assemblies complement our VDS Lite frame systems where doors are desired. Ask about options to provide the ideal glazing solution for a temp rise door with best vision area.

TECHNICAL SPECIFICATIONS

Testing/Standard Conformity	UL 10B, UL 10C, NFPA 80, 252, ASTM N/A, CAN/ULC-S104
Finish Options	Powder Coat/Enamel/Kynar
Custom Colors ¹	Yes
Fabrication	Welded
Certification	Underwriters Laboratories - UL LLC
Fabricated in the US	Yes
Single/Double Doors	Yes (see VDS Doors)
Weight (lbs/lin. ft; kg/lin. ft.)	2 (0.9) (does not include glass) *Weight per unit provided prior to shipment*

MAXIMUM DIMENSIONS

D.L.O. size limitations dependent on maximum exposed glass area

Maximum Height (in.; m)	96 (2.438) Call for details
Maximum Width (in.; m)	42 (1.067) Call for details

DETAILS



¹Surcharge may apply

Rev. 11.11.15 The information published in this document is correct at the time of going to press. Such information may be subject to change and products may be modified.